

PRODUCT DATASHEET

R2 Fire Rated Downlight (R2 Dimmable)

PRODUCT DATA

Range	LED Downlights
Part Code(s)	R095501 R095502
Applications	Interior
Warranty	5 years
Certification(s)	CE, RoHS

PHYSICAL DATA

Colour Finish	<ul style="list-style-type: none">WhiteGunmetal GreyPolished Chrome
Dimensions (mm)	Ø85 x H75
Luminaire Fixing	Recessed
Construction Material	Aluminium
Diffuser Type	Polycarbonate (TPa rated)
Unit Weight	0.35Kg

ELECTRICAL DATA


Wattage	8W
Voltage Range	AC220-240
Power Factor	>0.50
Inrush Current	<60A
Running Current	DC350mA

PERFORMANCE DATA


Colour Temperature	3000K 4000K
Lumens (±5%)	801
Efficacy	~100Lm/W
Operating Temperature	-20°C to +40°C
Beam Angle	38°
Operating Hours	>50000
CRI	>85Ra
IP Rating	IP65
IK Rating	IK08
Dimming	R2Dimmable (3 step analog dimming 100% - 50% - 10% Contact RICOMAN for more details)
Fire Rated	Yes
Flicker-free	Yes



INTERCHANGEABLE
(All bezels included in the packaging)



Easy Twist and Lock Mechanism



Hole Size: 70 mm

